New Fire Alarm System

a t

Gerhardt Civic Center

for


City of Moraine

3050 Kreitzer Road Moraine, Ohio 45439

January 6, 2020

Helmig Lienesch LLC Consulting Engineers


410 South Jefferson Street (937) 228-4007 Dayton, Ohio 45402 FAX: (937) 228-1936



SHEET INDEX

FA-0 FIRE ALARM - LEGEND, NOTES, DETAILS

FA-1 FIRE ALARM - FLOOR PLAN



Bids Due: January 22, 2020


Z – 2#18 (ZONE)

- ALL WIRE MUST MEET NEC-760 FOR POWER LIMITED SYSTEMS.

- ALL EQUIPMENT SHALL BE INSTALLED AND TESTED IN ACCORDANCE WITH NFPA-72 STANDARDS.

- THERE MUST BE NO AC POWER IN THE FIRE ALARM CONDUIT.

- THE HEIGHT OF THE MANUAL FIRE ALARM BOXES SHALL BE A MINIMUM OF 42" AND A MAXIMUM OF 48", MEASURED



FIRE ALARM RISER DIAGRAM





REFERENCE TO DETAIL

NOTE SYMBOL CANDELA RATING

FIRE ALARM VISUAL SIGNAL (STROBE) @80"A.F.F. TO BOTTOM

FIRE ALARM AUDIO-VISUAL SIGNAL (HORN/STROBE) @80"A.F.F. TO BOTTOM

MANUAL PULL STATION @48"A.F.F. TO TOP

CEILING MOUNTED SMOKE DETECTOR

CEILING MOUNTED HEAT DETECTOR

ADDRESSABLE RELAY MODULE


HVAC UNIT SHUTDOWN DETECTOR (SEE NOTE 3)

FIRE ALARM CONTROL PANEL

FIRE ALARM REMOTE ANNUNCIATOR PANEL

GENERAL NOTES

- ALL FIRE ALARM CONTROL CABLES SHALL BE PLENUM RATED:
- CABLES ABOVE LAY-IN CEILINGS SHALL BE INSTALLED USING J-HOOKS SPACED APPX. 4'-0" O.C. MOUNTED ON STRUCTURE OR WALLS AT A HEIGHT THAT ALLOWS CEILING TILE REMOVAL.
- □ CABLES RUN IN MECHANICAL ROOMS, ELECTRICAL ROOMS, EQUIPMENT ROOMS, STORAGE ROOMS, AND OTHER AREAS WHERE CABLE IS SUBJECT TO DAMAGE ALL CABLE SHALL BE RUN IN MINIMUM 1" EMT.
- □ CABLES RUN EXPOSED IN CLASSROOMS, OFFICES, CORRIDORS, LOBBIES, CONFERENCE ROOMS, OR ANY FINISHED AREA IT SHALL BE RUN IN METALLIC, RECTANGULAR, WIREWAY AS MANUFACTURED BY WIREMOLD (500 OR 700 SERIES), PANDUIT, OR EQUAL. THE WIREWAY SHALL BE SECURELY MOUNTED TO WALLS, CEILING, ETC. THE WIREWAY SHALL BE IVORY TO MATCH BUILDING PAINT COLOR.
- WHERE FABRIC OR PANELED WALLS EXIST TAKE SPECIAL CARE NOT TO DAMAGE THE FINISH. IF DAMAGE OCCURS, REPAIR AS REQUIRED.
- C. ANY DAMAGED SURFACE SHALL BE FINISHED AND PAINTED (CORNER TO CORNER) TO MATCH EXISTING.



Cen Fir

410 South Jefferson Dayton, Ohio 45402

DRAWN BY: WLE CHECKED BY:


DATE: January 6, 2020

PROJECT NO:


SHEET NO:


FA-0

- 1 REMOVE EXISTING DUCT DETECTOR MONITORS AND REPAIR/PAINT WALL TO MATCH EXISTING. REMOVE ALL ABANDONED CONDUIT AND WIRE IN IT'S ENTIRETY. SALVAGE EXISTING BRANCH CIRCUIT TO SERVE NEW FACP. VERIFY THAT THIS BRANCH CIRCUIT IS DEDICATED FOR FACP ONLY.
- PROVIDE NEW FIRE ALARM CONTROL PANEL (FACP) ON 3/4" x 48"W x 96"H PLYWOOD EQUIPMENT BACKBOARD PAINTED ALL SIDES WITH GRAY FIRE-RETARDANT PAINT.
- WIRE HVAC ZONE SMOKE DETECTORS TO SHUT DOWN ASSOCIATED HVAC UNIT, VIA ADDRESSABLE RELAY MODULE, WHEN SMOKE IS DETECTED. USE A NOTIFIER NC-100R RELAY MODULE TO SHUT DOWN THE HVAC UNITS.
- PROVIDE RELAY MODULES TO MONITOR EXISTING SPRINKLER AND OS&Y
 VALVE TAMPER SWITCHES AND KITCHEN HOOD SUPPRESSION SYSTEM. USE A
 NOTIFIER NMM-100P MONITOR RELAY FPR THESE APPLICATIONS.
- 5 SURFACE MOUNT REMOTE ANNUNCIATOR PANEL "RAP" CENTERED ON EXISTING WALL AT 60"A.F.F. TO CENTERLINE. RUN CABLE TO LAY-IN CEILING USING WIREMOLD RACEWAY.
- REMOVE EXISTING DUCT MOUNTED SMOKE DETECTOR, AND ASSOCIATED CONDUIT AND WIRE, AT EACH HVAC UNIT.









Gerhardt Civic Center

elmig Lienesch LL nsulting Engineers

DRAWN BY:

CHECKED BY:

DRH

DATE:

January 6, 2020

410 South Jefferson Dayton, Ohio 45402

PROJECT NO:

SHEET NO:

FA-1